

技术参数 Main Specification

Model 型号	ZB3060X16
Max.drilling diameter (on 45 steel) 最大钻孔直径(在45钢上) (mm)	φ 62
Max.drilling diameter (on HT200 cast iron) 最大钻孔直径(在HT200铸铁上) (mm)	φ 72
Max.tapping diameter (on 45 steel) 最大攻丝直径(在45钢上)	M46
Max.tapping diameter (on HT200 cast iron) 最大攻丝直径(在HT200铸铁上)	M52
Max.distance from spindle to generating line of column 主轴中心线至立柱母线距离 (mm)	350-1600
Distance of horizontal movement for spindle box (manual) 主轴箱水平移动距离(手动) (mm)	1250
Max.distance between spindle end to the worktable surface of the base 主轴端面至底座工作面距离(mm)	350-1250
Max.travel of the spindle 主轴最大行程(mm)	315
Spindle taper bore 主轴孔锥度号	MT. 5
Spindle speed step 主轴转速级数	Stepless
Spindle speed range 主轴转速范围(r/min)	38-275 275-2000
Spindle feed steps 主轴进给量级数	8
Spindle feed range 主轴进给量范围(mm/r)	0.06-1.00
Speed of rocker arm up and down movement 摇臂升降速度(m/min)	1.2
Rotation angle of rocker arm 摇臂回转角度(degree)	±180
Distance of spindle movement for calibrated dial each revolution 刻度盘每转主轴移动距离(mm)	122
Power of main motor (tranducer motor) 主电机功率(变频电机) (KW)	4
Power of motor for rocker arm up and down movement 摇臂升降电机功率(KW)	1.1
Power of oil pump motor for spindle box, column and rocker arm clamping 主轴箱、立柱、摇臂夹紧油泵电机功率(KW)	0.75
Weight of machine(without worktabke) 机床毛重(不含工作台) (Kg)	3500
Machine dimension (L X W X H) 机床轮廓尺寸(长X宽X高) (mm)	2490x1000x2598